

Constant current DALI LED driver



Features特征:

- The output current is constant;输出模式: 恒流;
- Input voltage:170-265VAC;输入电压: 170-265VAC;
- Using active built-in PFC technology;采用PFC技术;
- Efficiency>88% PF>0.95;效率>88%功率因素PF>0.95;
- Protection:SCP/OVP/OCP;短路保护 过压保护 过流保护;
- Fireproof plastic case;塑料防火外壳;
- Fit for KNX/Tridonic/Siemens/Philips/Feelux system;
- Noise free,flicker free;无噪音, 无频闪;
- CE/ROHS/SAA/TUV passed;CE/ROHS/SAA/TUV认证;
- DALI IEC62386 design,compatible with DALI V1&V2; IEC62386国际通用标准设计, 兼容DALI V1和V2通信标准;
- 5 Years warranty,lifespan>50,000hrs.5年保, 寿命>5小时。

规格书Specification Sheet


名称Model	CC输出	参数Parameter	
输出 Output	输出电流 Output current	1200mA	1000mA
	恒流精度 Current precision	±5%	
	输出电压 Output voltage	27-42V	45-60V
	输出功率 Output Power	60W Max	
输入 Input	输入电压 Input Voltage Range	170-265V AC	
	输入电流 AC Current(Typ)	0.38A@180VAC 0.34A@200VAC 0.30A@230VAC 0.26A@264VAC	
	频率 Frequency Range	50/60Hz	
	功率因数	PF>0.95@220V	
	效率 Full-loading Efficiency	>88%	
异常保护 Protection	保护类型 Short Circuit	Short circuit protection / Over voltage protection	
	最大输入电压Over Voltage	<265VAC	
使用环境 Environment	工作温度Operation Temperature	-20—+45℃	
	工作湿度Operation Humidity	20-90%	
	存储 Storage	-40—+85℃, 10-95%RH	
	温度系数Temperature Coefficient	±0.03%/℃(0~50℃)	
	抗震能力Vibration Resistance	10~500HZ,2G 10Min/period,X、Y、Z line per 60 mins	
安规与电磁兼容 Safety&EMC	标准 Standard	Refer to EN 61347-1;EN 61347-2-13; EN 62493	
	耐压 Withstand Voltage	I/P-O/P:3.75KVAC	
	绝缘强度Insulating Strength	I/P-O/P:400M Ω/500 VDC/25℃/70%RH	
	传导 EMC Emission	To Correspond EN55015,EN61000-3-2(≧50% load)	
	辐射 EMC Immunity	To Correspond EN55015,EX61000-4-2,3,4,5,6,8,11,A Level of light industry standard(Surge 4KV)	
其他Other	重量Weight	200g	
	尺寸Dimension	155*53*30mm (L*W*H)	
	材质Material	94V-0 PC fire retardant	
	颜色Color	white	
	包装Packing	31*17*18cm/27pcs	

NOTE


All parameters are measured at normal temperature(25-28℃)
 1、Ripple & Noise are measured at 20KHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1 uf & 47uf parallel capacitor(@ full load).
 2、The efficiency measured at Max output voltage,and 230VAC with full load,if with 110VAC the efficiency will be lowered 0.5%~1.5%;Working 1~2 hours,efficiency will be higher 1.5%~1%than the initial stage.

Constant current DALI LED driver


1.Mechanical Specification



2.Power Factor Characteristics



3.Efficiency & Load of (110VAC / 230VAC)



4.DALI Dimming system

